



## INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

<p>(51) International Patent Classification <sup>6</sup> : <b>H04L 12/28, 12/413, H04B 7/26</b></p>	<p><b>A1</b></p>	<p>(11) International Publication Number: <b>WO 99/00932</b></p> <p>(43) International Publication Date: 7 January 1999 (07.01.99)</p>
<p>(21) International Application Number: PCT/IL98/00291</p> <p>(22) International Filing Date: 22 June 1998 (22.06.98)</p> <p>(30) Priority Data: 121179 27 June 1997 (27.06.97) IL</p> <p>(71) Applicant (for all designated States except US): ELPAS ELECTRO-OPTIC SYSTEMS LTD. [IL/IL]; Hasadma Street 11, Industrial Zone, 43650 Raanana (IL).</p> <p>(72) Inventors; and (75) Inventors/Applicants (for US only): RADOMSKY, Israel [IL/IL]; Poalei Zion 15, 46242 Herzlia (IL). LAVIE, Nokie [IL/IL]; Tirza Street 8, 44852 Ma'ale Shomron (IL).</p> <p>(74) Agent: REINHOLD COHN AND PARTNERS; P.O. Box 4060, 61040 Tel Aviv (IL).</p>		<p>(81) Designated States: AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, CA, CH, CN, CU, CZ, DE, DK, EE, ES, FI, GB, GE, GH, GM, GW, HU, ID, IL, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MD, MG, MK, MN, MW, MX, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, SL, TJ, TM, TR, TT, UA, UG, US, UZ, VN, YU, ZW, ARIPO patent (GH, GM, KE, LS, MW, SD, SZ, UG, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, ML, MR, NE, SN, TD, TG).</p> <p><b>Published</b> With international search report. Before the expiration of the time limit for amending the claims and to be republished in the event of the receipt of amendments.</p>
<p>(54) Title: METHOD AND SYSTEM FOR AVOIDING COLLISIONS IN AN INFRARED WIRELESS NETWORK</p> <div data-bbox="462 1144 1153 1606"> <pre> graph TD     18[COMMUNICATION DEVICE] --- 22[IR TRANSCEIVER]     20[COMMUNICATION DEVICE] --- 23[IR TRANSCEIVER]     21[COMMUNICATION DEVICE] --- 16[IR TRANSCEIVER]     22 --- 24[NIC]     23 --- 26[NIC]     16 --- 12[NIC]     24 --- 25[COMPUTER]     26 --- 27[COMPUTER]     12 --- 11[COMPUTER]     22 --- 14[COMMUNICATION DEVICE]     23 --- 15[COMMUNICATION DEVICE]     14 --- 13[HUB]     15 --- 13     13 --- 11 </pre> </div> <p>(57) Abstract</p> <p>A method and system for avoiding collision between data streams transmitted by at least a pair of wireless transmitters (16, 20, 21) operating on substantially equal frequencies and coupled via respective communication channels (17, 22, 23) to respective communication devices (14, 18, 19) having associated therewith respective carrier sense means (12, 28, 29) which are responsive to a signal received thereby for preventing the respective communication device from initiating or continuing transmission of data. According to the method whenever data is wireless transmitted by one of the transmitters, said one of the transmitters sending a fictitious data signal along the respective communication channel so as to be detected by the respective carrier sense means.</p>		

**FOR THE PURPOSES OF INFORMATION ONLY**

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AL	Albania	ES	Spain	LS	Lesotho	SI	Slovenia
AM	Armenia	FI	Finland	LT	Lithuania	SK	Slovakia
AT	Austria	FR	France	LU	Luxembourg	SN	Senegal
AU	Australia	GA	Gabon	LV	Latvia	SZ	Swaziland
AZ	Azerbaijan	GB	United Kingdom	MC	Monaco	TD	Chad
BA	Bosnia and Herzegovina	GE	Georgia	MD	Republic of Moldova	TG	Togo
BB	Barbados	GH	Ghana	MG	Madagascar	TJ	Tajikistan
BE	Belgium	GN	Guinea	MK	The former Yugoslav Republic of Macedonia	TM	Turkmenistan
BF	Burkina Faso	GR	Greece	ML	Mali	TR	Turkey
BG	Bulgaria	HU	Hungary	MN	Mongolia	TT	Trinidad and Tobago
BJ	Benin	IE	Ireland	MR	Mauritania	UA	Ukraine
BR	Brazil	IL	Israel	MW	Malawi	UG	Uganda
BY	Belarus	IS	Iceland	MX	Mexico	US	United States of America
CA	Canada	IT	Italy	NE	Niger	UZ	Uzbekistan
CF	Central African Republic	JP	Japan	NL	Netherlands	VN	Viet Nam
CG	Congo	KE	Kenya	NO	Norway	YU	Yugoslavia
CH	Switzerland	KG	Kyrgyzstan	NZ	New Zealand	ZW	Zimbabwe
CI	Côte d'Ivoire	KP	Democratic People's Republic of Korea	PL	Poland		
CM	Cameroon	KR	Republic of Korea	PT	Portugal		
CN	China	KZ	Kazakhstan	RO	Romania		
CU	Cuba	LC	Saint Lucia	RU	Russian Federation		
CZ	Czech Republic	LI	Liechtenstein	SD	Sudan		
DE	Germany	LK	Sri Lanka	SE	Sweden		
DK	Denmark	LR	Liberia	SG	Singapore		
EE	Estonia						

**Method and system for avoiding collisions  
in an Infra-Red wireless network**

**FIELD OF THE INVENTION**

This invention relates to wireless transmission within or between Local Area Networks (LANs) and, in particular, to an improved method of collision avoidance of data in such LANs.

5

**BACKGROUND OF THE INVENTION**

LANs employing non-wireless communication channels typically comprise a communication device in the form of a computer terminal connected to other communication devices by a twisted wire or coax or  
10 multi-core cable. In each communication device there is provided a suitable Network Interface Card (NIC) which operates in accordance with a network protocol for allowing different terminals to communicate with one another.

Various network protocols are known such as, for example, Ethernet, which not only control the manner in which data is transmitted from  
15 one terminal to another but also provide what is known as "collision detection" which detects the substantially simultaneous transmission of data from two or more network terminals.

Such collision detection is beneficial, because it permits near simultaneous transmission of data packets from two or more terminals to be aborted almost immediately when only a small fraction of the data packet has been transmitted. Were such collision detection not to be provided, then the whole of the data packet would be transmitted by each of the conflicting terminals and only then would the error checking algorithms, which are themselves an integral feature of the network protocol, detect that the received data was corrupt. This would then require controlled re-transmission of the data by each of the conflicting terminals in such a manner as to ensure that no two terminals attempted to transmit simultaneously. The manner in which this is done is well known to those skilled in the art and thus needs no further elaboration.

It is important to understand that the collision detection which is provided as part of the network protocol has no way of actually preventing data collision. All it can do is to detect that two or more terminals are transmitting simultaneously and abort all of the transmissions before a complete data packet is transmitted. This saves time and, of course, energy. The remedial action which is then taken, as well as its particular implementation, depends on the network protocol employed.

The ability to detect collisions of data packets transmitted by different terminals in a LAN wherein the communication devices (terminals) are interconnected via wires, is a consequence of such LANs operating "full duplex". In other words, a communication device is able both to send and receive data at the same time. Consequently, a transmitting terminal is nevertheless able to receive data transmitted by a competing terminal and the network protocol is then able to detect the resulting data collision and take appropriate remedial action.

In wireless communication, full duplex data transmission is not possible unless different frequencies are employed to transmit and receive

data so that different broadcast channels can be employed for data transmission and reception, respectively. Increasingly, wireless transmission is being effected using infra-red communication which operates on the same principles as radio transmission in that electromagnetic waves are employed, but only a very narrow part of the electromagnetic spectrum is employed. To all intents and purposes, the frequency of all infra-red transmissions can be considered equal. As a result, full duplex transmission using IR is not possible and, therefore, once data has been transmitted through the air by an IR transmitter, there is no way during the actual act of data transmission that the IR transmitter can know about a conflicting IR transmitter sending data simultaneously.

Owing to this inability of IR transmitters to detect data collisions, it is normal practice to employ sophisticated data communications protocols which detect that data received by a terminal is corrupt and then require that the transmitting terminal re-transmit the corrupted data packet in a controlled manner so as to avoid further collisions. This is wasteful of both time and energy. Thus, specifically, if a data packet contains 1,500 bytes of data which are transmitted in 1.5 ms, then seeing that all of the data packet must be transmitted in its entirety before the receiving software can determine that it has been received corruptly, no remedial action can be taken for at least 1.5 ms, whereupon the whole data packet must, of course, be re-transmitted in its entirety. On the other hand, with conventional wired LANs having collision detection hardware, a data collision can be detected typically within one or two bits of data so that the transmission of the complete packet may then be interrupted after no more than 200 ns. This is, of course, a very substantial saving in wasted time. Furthermore, since data transmission requires energy, being able to abort the data transmission when only a very small fraction of the data packet has been transmitted, also saves energy; and

this is particularly significant when portable, battery-powered IR transmitters are employed.

## SUMMARY OF THE INVENTION

5           It is therefore an object of the invention to provide a method for avoiding collision between data streams transmitted by at least two IR transmitters which are coupled via respective cables to a conventional LAN.

          According to a broad aspect of the invention, there is provided a method for avoiding collision between data streams transmitted by at least a  
10   pair of wireless transmitters operating on substantially equal frequencies and coupled via respective communication channels to respective communication devices having associated therewith respective carrier sense means which are responsive to a signal received thereby for preventing the respective communication device from initiating or continuing transmission of data, the  
15   method comprising the steps of:

          whenever data is wireless transmitted by one of the transmitters, said one of the transmitters sending a fictitious data signal along the respective communication channel so as to be detected by the respective carrier sense means.

20           Preferably, the carrier sense means comprises a conventional Network Interface Card (NIC) which is, in any case, provided as an integral part of the LAN. In such case, the provision of the NIC is exploited by the method according to the invention in order to "deceive" the receiving terminal into believing that a conventional data transmission was initiated by another  
25   terminal in the LAN.

          The invention exploits the Carrier Sense Multiple Access (CSMA) protocol in which collision avoidance is implemented in the Ethernet network and other networks having similar protocols. Before transmitting, each transmitter establishes that no transmission has been in progress for at least a

minimum time interval, typically 9.6  $\mu$ s. Only after this time interval has elapsed in the absence of any network activity, is a transmitter permitted to initiate a new transmission. In the method according to the invention, after this time interval has elapsed, the wireless IR LAN starts to transmit fictitious  
5 data to the NIC and thus ensures collision avoidance. Specifically, the terminal containing the NIC is deceived into interpreting the received fictitious data as regular network activity and is thus prevented from initiating its own transmission.

## 10 BRIEF DESCRIPTION OF THE DRAWINGS

In order to understand the invention and to see how the same may be carried out in practice, a preferred embodiment will now be described, by way of non-limiting example only, and with reference to the accompanying drawings, in which:

15 **Fig. 1** is a block diagram showing functionally a system for carrying out the method of the invention; and

**Fig. 2** shows part of a timing diagram assuming the use of the Ethernet communications protocol for use with the system illustrated in Fig. 1.

## 20 DETAILED DESCRIPTION OF A PREFERRED EMBODIMENT

Fig. 1 shows an infra-red LAN designated generally as 10, comprising a computer 11 operating as a network server containing therein a Network Interface Card (NIC) 12. The computer 11 is coupled via a HUB 13 to a first communication device 14 by means of a 10 Base-T (twisted pair)  
25 cable 15 constituting a communication channel. The HUB 13 is a wired distribution box allowing routing to other communication devices in the system. A first IR transceiver 16 is coupled to the first communication device 14 by a cable 17 which also constitutes a communication channel. The first IR transceiver 16 allows the first communication device 14 to communicate

via wireless communication with second and third communication devices 18 and 19, respectively. To this end, there are connected to the second and third communication devices 18 and 19, corresponding second and third IR transceivers 20 and 21 via respective 10 Base-T (twisted pair) cables 22 and 5 23 which also constitute communication channels. Likewise, there are connected to the second and third communication devices 18 and 19, via respective 10 Base-T (twisted pair) cables 24 and 25 which also constitute communication channels, corresponding second and third computers 26 and 27 containing therein respective Network Interface Cards (NIC) 28 and 29.

10           When one of the communication devices 14, 18 or 19 receives a communication from one of the other communication devices in the LAN, the resulting signal passes along the adjacent communication channel 15, 24 and 25 so as to be received by the NICs 12, 28 and 29 in each of the computers 11, 26 and 27 which then acts, in known manner, to prevent the respective 15 communication device 14, 18 and 19 from initiating a communication. By such means, overlapping communications between different communication devices in the LAN 10 is prevented.

          When one of the IR transceivers, for example the first IR transceiver 16, initiates a communication, a fictitious data signal is sent along 20 the respective communication channel 17 so as to be received the NIC 12 in the respective computer 12 in the LAN 10. The NIC 12 ensures that the computer 12 does not attempt to initiate further communication until the IR transceiver 16 has terminated its transmission. Upon such termination, discrete, non-overlapping time slots are randomly selected by each of the IR 25 transceivers 16, 17 and 18 so that no two IR transceivers will attempt to initiate a communication simultaneously. Such simultaneous initiation of a data communication by the IR transceivers must be prevented because, as explained above, an IR transceiver which is engaged in data transmission has no way of detecting that another IR transceiver in the LAN 10 has also,



simultaneously, initiated a data transmission. Thus, by virtue of the random time delay selected by each NIC which wants to initiate transmission, the likelihood of two or more IR Transceivers attempting to initiate a communication simultaneously is significantly reduced.

5           Fig. 2 shows a detail of a timing diagram assuming the use of the Ethernet communications protocol in the wired communication channels of the LAN 10. IR data is transmitted by a station transmitter Tx in packets, as shown at 30. At the end of each data packet 30, each station receiver Rx waits for a period of dead time  $\Delta t$  and then selects a random time slot for  
10   initiating communication. The dead time  $\Delta t$  is a feature of the Ethernet protocol and merely provides for a minimal inter-frame time gap. In order to ensure that during the time interval following the end of one data packet until the initiation of the next data packet, none of the communication devices attempts to initiate its own communication, fictitious data is sent to each of  
15   the NICs by the corresponding station transmitter Tx. The fictitious data is interpreted by the receiving NIC as a regular wired data transfer through the 10 Base-T (twisted pair) cable communication channel. As a result, in order to avoid collisions, the NIC acts to prevent the communication channel from initiating further communication. By such means wireless communication  
20   can be implemented without the danger of collision from wired data transmission through the LAN 10; whilst the random allocation of time slots for the wireless data transfer likewise serves to reduce the likelihood of data collisions during IR data transmission.

          Furthermore, because the invention obviates the need for protocol  
25   conversion and verification, wireless data received by the communications device may be forwarded on the fly to a destination computer containing a NIC card, without the need for buffering and processing. This results in faster and less expensive data transfer.

**CLAIMS:**

1. A method for avoiding collision between data streams transmitted by at least a pair of wireless transmitters (16, 20, 21) operating on substantially equal frequencies and coupled via respective communication  
5 channels (17, 22, 23) to respective communication devices (14, 18, 19) having associated therewith respective carrier sense means (12, 28, 29) which are responsive to a signal received thereby for preventing the respective communication device from initiating or continuing transmission of data, the method comprising the step of:  
10 whenever data is wireless transmitted by one of the transmitters, said one of the transmitters sending a fictitious data signal along the respective communication channel so as to be detected by the respective carrier sense means.
2. The method according to Claim 1, wherein the wireless transmit-  
15 ters are infra-red transmitters (16, 20, 21).
3. The method according to Claim 1 or 2, wherein the carrier sense means (12, 28, 29) comprises a Network Interface Card (NIC) containing therein a carrier sense and anti-collision protocol.
4. The method according to any one of the preceding claims, further  
20 including the step of allocating a random time slot to each of the wireless transmitters for initiating a data transmission therein so as to reduce a probability of two transmitters starting to transmit simultaneously.
5. An infra-red LAN (10) comprising at least a pair of IR transmitters (16, 20, 21) coupled via respective communication channels (17, 22, 23) to  
25 respective communication devices (14, 18, 19) having associated therewith respective carrier sense means (12, 28, 29) which are responsive to a signal received thereby for preventing the respective communication device from initiating or continuing transmission of data, each of the IR transmitters being

programmed to carry out the collision avoidance method of any one of the preceding claims.

6. The infra-red LAN according to Claim 5, wherein at least one of the communication devices is a network HUB (13).

- 5 7. The infra-red LAN according to Claim 5 or 6, wherein at least one of the communication devices is a computer (11, 26, 27) containing a network card (12, 28, 29) therein.




Fig. 1




Fig. 2

# INTERNATIONAL SEARCH REPORT

Internatic Application No <b>PCT/IL 98/00291</b>		
<b>A. CLASSIFICATION OF SUBJECT MATTER</b> IPC 6 H04L12/28 H04L12/413 H04B7/26		
According to International Patent Classification (IPC) or to both national classification and IPC		
<b>B. FIELDS SEARCHED</b> Minimum documentation searched (classification system followed by classification symbols) IPC 6 H04L		
Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched		
Electronic data base consulted during the international search (name of data base and, where practical, search terms used)		
<b>C. DOCUMENTS CONSIDERED TO BE RELEVANT</b>		
Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
Y	EP 0 475 682 A (NCR CO) 18 March 1992 see column 2, line 8 - line 53 see column 7, line 51 - column 8, line 44 see column 9, line 45 - line 50	1-5,7
A	---	6
Y	WO 96 19877 A (3COM CORP) 27 June 1996 see page 13, line 31 - page 14, line 22	1-5,7
A	"STANDARD PC-NET ADAPTER AND SOFTWARE CSMA OR CSMA/CA ON NON-TRADITIONAL MEDIA" IBM TECHNICAL DISCLOSURE BULLETIN, vol. 35, no. 3, 1 August 1992, pages 105-108, XP000326192 see the whole document ---	1-7
-/--		
<input checked="" type="checkbox"/> Further documents are listed in the continuation of box C. <input checked="" type="checkbox"/> Patent family members are listed in annex.		
* Special categories of cited documents : <div style="display: flex; justify-content: space-between;"> <div style="width: 45%;"> <p>"A" document defining the general state of the art which is not considered to be of particular relevance</p> <p>"E" earlier document but published on or after the international filing date</p> <p>"L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)</p> <p>"O" document referring to an oral disclosure, use, exhibition or other means</p> <p>"P" document published prior to the international filing date but later than the priority date claimed</p> </div> <div style="width: 45%;"> <p>"T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention</p> <p>"X" document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone</p> <p>"Y" document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art.</p> <p>"&amp;" document member of the same patent family</p> </div> </div>		
Date of the actual completion of the international search  <div style="text-align: center; font-weight: bold;">19 October 1998</div>		Date of mailing of the international search report  <div style="text-align: center; font-weight: bold;">27/10/1998</div>
Name and mailing address of the ISA European Patent Office, P.B. 5818 Patentlaan 2 NL - 2280 HV Rijswijk Tel. (+31-70) 340-2040, Tx. 31 651 epo nl, Fax: (+31-70) 340-3016		Authorized officer  <div style="text-align: center; font-weight: bold;">Mikkelsen, C</div>

# INTERNATIONAL SEARCH REPORT

Internatic Application No  
PCT/IL 98/00291

C.(Continuation) DOCUMENTS CONSIDERED TO BE RELEVANT		
Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
A	<p>WO 96 21978 A (MOMENTUM MICROSYSTEMS ;LANSFORD JAMES L (US); MUECKE MICHAEL L (US) 18 July 1996 see page 4, line 10 - page 5, line 5 see page 8, line 24 - line 37 see page 10, line 18 - page 12, line 5 -----</p>	1-7

# INTERNATIONAL SEARCH REPORT

Information on patent family members

International Application No

PCT/IL 98/00291

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
EP 0475682 A	18-03-1992	DE 69126266 D	03-07-1997
		DE 69126266 T	02-01-1998
		JP 6029978 A	04-02-1994
		US 5369639 A	29-11-1994
WO 9619877 A	27-06-1996	US 5657326 A	12-08-1997
		AU 4603996 A	10-07-1996
		GB 2310978 A	10-09-1997
WO 9621978 A	18-07-1996	EP 0803152 A	29-10-1997